

40E Series - Endless Design Single Duty - Deli

- PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

**Self-Contained
Remote**

**SC-CDS40E-8
R-CDS40E-8**

**SC-CDS40E-12
R-CDS40E-12**

Length with (2) ends

100-1/2"

148-1/2"

Length without ends

96"

144"

Height with ends

53"

53"

Height without ends

52-1/2"

52-1/2"

Depth with ends

40"

40"

Depth without ends

39-1/2"

39-1/2"

Endless Design

YES

YES

(Dimensions are +/-1/4")

- Specification subject to change without notice

Standard Specifications and Optional Features

| | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>CONSTRUCTION UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Triple pane insulated front glass- 28"H Heavy gauge steel super structure Single duty display Endless design allows for continuous line up Drain is included for cleaning</p> | <p>FINISHES Satin finish extrusion on doors and door tracks Designer white exterior front and ends Stainless steel mirror trim Stainless steel heavy gauge top- 20" W Rear of unit is stainless steel brush finish at top Bottom rear is designer white aluminum</p> |
| <p>INTERIOR Designer white interior ends Stainless steel heavy gauge mezzanine shelf (1row) Epoxy coated main deck shelves Air insulated baffle (<i>prevents moisture from dripping into display area</i>)</p> | <p>REFRIGERATION Copevap system (<i>eliminates need for condensate pan</i>) R134a expansion valve system Gravity coil located at <i>inside top of unit and</i> Self contained system Automatic defrost controlled by time clock-(<i>self contained units only</i>) Pressure control maintains constant temperatures Remotes available</p> |
| <p>EXTERIOR Double pane rear removable doors Newly designed compression door jamb Removable front grille allows for cleaning Removable rear grille for easy servicing 2-1/4" removable end panels Front bumper 1"- gray</p> | <p>LIGHTING 2 Rows of T12 lighting at top of unit</p> |
| <p>ELECTRICAL REQUIREMENTS 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed 115V-12AMP general purpose receptacle (<i>wired separately</i>)</p> | <p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p> |

OPTIONAL FEATURES

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>Scale stand Paper cutter Stainless steel, laminate, or paint Mirrored doors Extra stainless steel mezzanine shelf</p> | <p>Drop work shelf Door locks Digital thermometer Sandwich racks Salad pan settings Front bumpers 3"</p> |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|



Technical Data

| Model | Self contained | SC-CDS40E-8 | SC-CDS40E-12 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| | Remote | R-CDS40E-8 | R-CDS40E-12 |
| Length with (2) ends Length without ends Height with ends Height without ends Depth with ends Depth without ends Endless design (Dimensions are +/- 1/4") | | 100-1/2" 96" 53" 52-1/2" 40" 39-1/2" YES | 148-1/2" 144" 53" 52-1/2" 40" 39-1/2" YES |
| Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH Defrost per day (24 hours) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage- lights only Cord and plug | Self contained Self contained Air Defrost Remote Self Contained Remote | 36°F to 40°F R134a 1/2 30 12 1 per day 2800 115V 11.2A 1.6A No | 36°F to 40°F R134a 3/4 30 12 1 per day 4200 115V 17.4A 2.4A No |
| Exterior color Interior color Inside end panels Floors # of top doors Door size # of coils Bottom storage Front glass # of main deck shelves Shelf size Cubic capacity (ft ³) Mezzanine- shelf | | White Stainless White White 4 20-1/2"X23-1/2" 1 No 28"X94-11/16" 4 23-1/2"X32-5/8" 49 Standard | White Stainless White White 4 31"X23-1/2" 1 No 28"X142-11/16" 6 23-1/2"X32-5/8" 74 Standard |

SHIPPING INFORMATION

| | | | |
|--------------|----------------|--------------------|--------------------|
| Height | | 58" | 58" |
| Depth | | 47" | 47" |
| Length | | 109" | 157" |
| Gross weight | Self contained | 983# | 1396# |
| | Remote | 890# | 1325# |
| Cubic feet | | 170ft ³ | 245ft ³ |

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Cases are equipped with washout drains; check your local building codes for connection requirements.
- Specification subject to change without notice