

RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

• PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIN2-24	RIN3-24	RIN4-24	RIN5-24
Length with ends	54-7/8"	78-7/8"	102-3/8"	126-1/8"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends	35-1/2"	35-1/2"	35-1/2"	35-1/2"
(Dimensions are +/-1/4")				

- Specification subject to change without notice

RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

Standard Specifications and Optional Features

<p>CONSTRUCTION UL Classified to ANSI/NSF 7 Heavy duty construction CFC free foamed in place insulation 2, 3, 4, or 5 door models available Inset door assembly Endless for continuous line ups</p>	<p>FINISHES Frame assembly and door - Anthony style 101 Exterior-designer white Interior-designer white</p>
<p>INTERIOR White ends Back is a combination of <i>white and perforated aluminum</i> Removable floor racks 5 heavy duty white epoxy shelves per door</p>	<p>REFRIGERATION Remote with R22 expansion valve Coil and fans located below floor pans</p>
<p>EXTERIOR White aluminum ends and fronts Double pane glass doors 24"X63" Black kick plate</p>	<p>LIGHTING 60" fluorescent lamps 2 Dr = 3 lights 3 Dr = 4 lights 4 Dr = 5 lights 5 Dr = 6 lights</p>
<p>ELECTRICAL REQUIREMENTS Fans and lighting - 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed</p>	<p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p>

OPTIONAL FEATURES

<p>Stainless steel, laminate or paint Digital thermometer Door swing change Insulated divider Plexiglas divider</p>	<p>Door locks Special door frames Temperature control thermostat Joint kit</p>
---	---



RIN Endless Design - Glass Door Reach In Refrigerators with 24" Wide Doors

Technical Data

Model	Remote	RIN2-24	RIN3-24	RIN4-24	RIN5-24
Length Height Depth (Dimensions are +/- 1/4")		54-7/8" 78-1/2" 35-1/2"	78-7/8" 78-1/2" 35-1/2"	102-3/8" 78-1/2" 35-1/2"	126-1/8" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) BTU's at +20°F Evap. Temp. Voltage Amperage Cord and plug		36°F to 40°F R22 2473 115V 4.4A No	36°F to 40°F R22 3471 115V 6.2A No	36°F to 40°F R22 4481 115V 8.0A No	36°F to 40°F R22 5522 115V 9.9A No
Exterior color Interior color Inside end panels Floor-removable deck pans Drain required Total shelves Door size		White White White White Yes 10 24"X63"	White White White White Yes 15 24"X63"	White White White White Yes 20 24"X63"	White White White White Yes 25 24"X63"

SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		61"	86"	107"	134"
Depth		43"	43"	43"	43"
Gross weight		568#	832#	1096#	1360#
Cubic feet		125ft ³	177ft ³	221ft ³	276ft ³

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

• PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIF2-24	RIF3-24	RIF4-24	RIF5-24
Length with ends	54-7/8"	78-7/8"	102-3/8"	126-1/8"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends	35-1/2"	35-1/2"	35-1/2"	35-1/2"

(Dimensions are +/-1/4")

- Specification subject to change without notice

RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

Standard Specifications and Optional Features

<p>CONSTRUCTION UL Classified to ANSI/NSF 7 Heavy duty construction CFC free foamed in place insulation 2, 3, 4, or 5 door models available Inset door assembly Endless for continuous line ups</p>	<p>FINISHES Frame assembly and door - Anthony style 101 Exterior-designer white Interior-designer white</p>
<p>INTERIOR White ends Back is a combination of <i>white and perforated aluminum</i> Removable floor racks 5 heavy duty white epoxy shelves per door</p>	<p>REFRIGERATION Remote with R404A expansion valve Coil and fans located below floor pans</p>
<p>EXTERIOR White aluminum ends and fronts Triple pane glass doors 24"X63" Black kick plate</p>	<p>LIGHTING 60" fluorescent lamps 2 Dr = 3 lights 3 Dr = 4 lights 4 Dr = 5 lights 5 Dr = 6 lights</p>
<p>ELECTRICAL REQUIREMENTS Electric defrost and defrost termination Standard 230V/60Hz/3Ph Fans and lighting 115V/60Hz/1ph Unit must be hard wired UL/CUL listed</p>	<p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p>

OPTIONAL FEATURES

<p>Stainless steel, laminate or paint Digital thermometer Door swing change Insulated divider Plexiglas divider</p>	<p>Door locks Special door frames Hot gas defrost Temperature control thermostat Joint kit</p>
---	--



RIF Endless Design - Glass Door Reach In Freezers with 24" Wide Doors

Technical Data

Model	Remote	RIF2-24	RIF3-24	RIF4-24	RIF5-24
Length Height Depth (Dimensions are +/- 1/4")		54-7/8" 78-1/2" 35-1/2"	78-7/8" 78-1/2" 35-1/2"	102-3/8" 78-1/2" 35-1/2"	126-1/8" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) Defrost per day (24 hours) BTU's at -25°F Evap. Temp. BTU's at -35°F Evap. Temp. Voltage Amperage Cord and plug	1 Defrost	0°F to -10°F R404A 1 3840 3980 115/230V 9.1/5.4A No	0°F to -10°F R404A 1 5577 5829 115/230V 10.8/8.2A No	0°F to -10°F R404A 1 7173 7500 115/230V 15.6/11.1A No	0°F to -10°F R404A 1 8829 9231 115/230V 18.0/13.9A No
Exterior color Interior color Inside end panels Floor-removable deck pans Drain required Total shelves Door size		White White White White Yes 10 24"X63"	White White White White Yes 15 24"X63"	White White White White Yes 20 24"X63"	White White White White Yes 25 24"X63"

SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		61"	86"	107"	134"
Depth		43"	43"	43"	43"
Gross weight		729#	1031#	1333#	1635#
Cubic feet		125ft ³	177ft ³	221ft ³	276ft ³

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

RIN Endless Design - Glass Door Reach In Refrigerators with 30" Wide Doors

- PRODUCT SPECIFICATIONS SHEETS



- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIN2-63	RIN3-63	RIN4-63	RIN5-63
Length with ends	68"	98-1/2"	128-1/2"	162"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends (Dimensions are +/-1/4")	35-1/2"	35-1/2"	35-1/2"	35-1/2"

- Specification subject to change without notice

RIN Endless Design - Glass Door Reach In Refrigerators with 30" Wide Doors

Standard Specifications and Optional Features

<p>CONSTRUCTION UL Classified to ANSI/NSF 7 Heavy duty construction CFC free foamed in place insulation 2, 3, 4, or 5 door models available Inset door assembly Endless for continuous line ups</p>	<p>FINISHES Frame assembly and door - Anthony style 101 Exterior-designer white Interior-designer white</p>
<p>INTERIOR White ends Back is a combination of <i>white and perforated aluminum</i> Removable floor racks 5 heavy duty white epoxy shelves per door</p>	<p>REFRIGERATION Remote with R22 expansion valve Coil and fans located below floor pans</p>
<p>EXTERIOR White aluminum ends and fronts Double pane glass doors 30"X63" Black kick plate</p>	<p>LIGHTING 60" fluorescent lamps 2 Dr = 3 lights 3 Dr = 4 lights 4 Dr = 5 lights 5 Dr = 6 lights</p>
<p>ELECTRICAL REQUIREMENTS Fans and lighting - 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed</p>	<p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p>

OPTIONAL FEATURES

<p>Stainless steel, laminate or paint Digital thermometer Door swing change Insulated divider Plexiglas divider</p>	<p>Door locks Special door frames Temperature control thermostat Joint kit</p>
---	---



RIN Endless Design - Glass Door Reach In Refrigerators with 30" Wide Doors

Technical Data

Model	Remote	RIN2-63	RIN3-63	RIN4-63	RIN5-63
Length Height Depth (Dimensions are +/-1/4")		68" 78-1/2" 35-1/2"	98-1/2" 78-1/2" 35-1/2"	128-1/2" 78-1/2" 35-1/2"	162" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) BTU's at +20°F Evap. Temp. Voltage Amperage Cord and plug		36°F to 40°F R22 2840 115V 3.9A No	36°F to 40°F R22 4064 115V 5.6A No	36°F to 40°F R22 5206 115V 7.0A No	36°F to 40°F R22 6439 115V 8.7A No
Exterior color Interior color Inside end panels Floor Drain required Total shelves Door size		White White White White Yes 10 30"X63"	White White White White Yes 15 30"X63"	White White White White Yes 20 30"X63"	White White White White Yes 25 30"X63"

SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		74"	107"	134"	171"
Depth		43"	43"	43"	43"
Gross weight		680#	1000#	1360#	1700#
Cubic feet		153ft ³	221ft ³	277ft ³	353ft ³

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice

RIF Endless Design - Glass Door Reach In Freezers with 30" Wide Doors

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Remote	RIF2-63	RIF3-63	RIF4-63	RIF5-63
Length with ends	68"	98-1/2"	128-1/2"	162"
Height	78-1/2"	78-1/2"	78-1/2"	78-1/2"
Depth with ends (Dimensions are +/-1/4")	35-1/2"	35-1/2"	35-1/2"	35-1/2"

• Specification subject to change without notice

RIF Endless Design - Glass Door Reach In Freezers with 30" Wide Doors

Standard Specifications and Optional Features

<p>CONSTRUCTION UL Classified to ANSI/NSF 7 Heavy duty construction CFC free foamed in place insulation 2, 3, 4, or 5 door models available Inset door assembly Endless for continuous line ups</p>	<p>FINISHES Frame assembly and door - Anthony style 101 Exterior-designer white Interior-designer white</p>
<p>INTERIOR White ends Back is a combination of <i>white and perforated aluminum</i> Removable floor racks 5 heavy duty white epoxy shelves per door</p>	<p>REFRIGERATION Remote with R404A expansion valve Coil and fans located below floor pans</p>
<p>EXTERIOR White aluminum ends and fronts Triple pane glass doors 30"X63" Black kick plate</p>	<p>LIGHTING 60" fluorescent lamps 2 Dr = 3 lights 3 Dr = 4 lights 4 Dr = 5 lights 5 Dr = 6 lights</p>
<p>ELECTRICAL REQUIREMENTS Electric defrost and defrost termination Standard 230V/60Hz/3Ph Fans and lighting 115V/60Hz/1Ph Unit must be hard wired UL/CUL listed</p>	<p><i>Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity.</i></p> <p><i>Important Note: Product must be cooled before being displayed within the case.</i></p>

OPTIONAL FEATURES

<p>Stainless steel, laminate or paint Digital thermometer Door swing change Insulated divider Plexiglas divider</p>	<p>Door locks Special door frames Hot gas defrost Temperature control thermostat Joint kit</p>
---	--



RIF Endless Design - Glass Door Reach In Freezers with 30" Wide Doors

Technical Data

Model	Remote	RIF2-63	RIF3-63	RIF4-63	RIF5-63
Length Height Depth (Dimensions are +/-1/4")		68" 78-1/2" 35-1/2"	98-1/2" 78-1/2" 35-1/2"	128-1/2" 78-1/2" 35-1/2"	162" 78-1/2" 35-1/2"
Operating temperature Refrigerant (expansion valve) Defrost per day (24 hours) BTU's -25°-EvapTemp. BTU's -35°-EvapTemp. Voltage Amperage Cord and plug	1 DEFROST	0°F to -10°F R404A 1 4653 4873 115/230V 6.5/6.9 No	0°F to -10°F R404A 1 6550 6866 115/230V 9.1/10.1 No	0°F to -10°F R404A 1 8484 8897 115/230V 11.2/13.1 No	0°F to -10°F R404A 1 10450 10961 115/230V 14.2/17.0 No
Exterior color Interior color Inside end panels Floor Drain required Total shelves Door size		White White White White Yes 10 30"X63"	White White White White Yes 15 30"X63"	White White White White Yes 20 30"X63"	White White White White Yes 25 30"X63"

SHIPPING INFORMATION

Height		83"	83"	83"	83"
Length		74"	107"	134"	171"
Depth		43"	43"	43"	43"
Gross weight		818#	1160#	1635#	1980#
Cubic feet		153ft ³	221ft ³	277ft ³	353ft ³

- Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- Specification subject to change without notice